



Home About Us QC Certification Products Terms & Conditions Eng. FAQs RFQ Contact Us

ROTARY POTENTIOMETERS

ROTARY POTENTIOMETER										
MODEL NUMBER	DIA. (7) (inches)	TYPE (2)	RESISTANCE RANGE ohms	TOL. ±	LIN. IND. (6) ±	W(8)	ANGLE		OPERATING TEMP.° (centigrade)	TORQUE OZ-IN.
							ELEC.°	MECH.°		
50-M123	1/2	WW	10 - 100K	5%	3%	1.5	325	325	-55 TO 135	1.0 - 8.0
50-M124	1/2	WW	50 - 25K	5%	3%	1.5	325	325	-55 TO 175	1.0 - 8.0
50-M125	1/2	WW	50 - 50K	5%	2.0% - 0.7%	1.5	325	325	-55 TO 135	6.0
50-M126	1/2	WW	50 - 50K	5%	1.3% - 0.25%	1.0	353	360 (1)	-55 TO 135	2.0
50-M490	1/2	WW	250 - 20K	5%	0.5%	2.0	354	360 (1)	-55 TO 105	0.05
50-P508	1/2	CP	1K - 25K	20%	0.5%	0.5	340	360 (1)	-55 TO 105	0.5
75-M90	3/4	WW	50 - 100K	5%	2.0% - 0.5%	2.0	320	335	-55 TO 135	3.0 - 8.0
75-M91	3/4	WW	50 - 100K	5%	2.0% - 0.5%	2.0	350	360 (1)	-55 TO 135	1.0
75-M92	3/4	WW	50 - 25K	5%	1.2% - 0.25%	2.0	350	360(1)	-55 TO 135	1.2
87-M42	7/8	WW	50 - 50K	3%	1.5% - 0.5%	2.0	320	330	-55 TO 135	0.3
87-M43	7/8	WW	50 - 50K	3%	1.5% - 0.5%	2.0	320	330	-55 TO 135	2.0
87-M44	7/8	WW	50 - 50K	3%	1.0% - 0.15%	2.0	353	360 (1)	-55 TO 135	0.1
87-P82	7/8	CP	500 - 50K	20%	2.0%	1.0	340	360 (1)	-55 TO 105	0.6
87-P83	7/8	CP	500 - 50K	10%	0.5%	1.0	340	360 (1)	-55 TO 105	0.35
106-M9	1-1/16	WW	50 - 50K	3%	1.2% - 0.5%	2.5	320	330	-55 TO 135	2.0 - 8.0
106-M10	1-1/16	WW	100 - 20K	3%	0.5% - 0.15%	2.5	353	360 (1)	-55 TO 135	0.15
112-P16	1-1/8	CP	250 - 100K	20%	2.0%	1.0	340	360 (1)	-55 TO 105	0.6
112-P17	1-1/8	CP	250 - 50K	20%	2.0%	1.0	340	360 (1)	-55 TO 105	0.5
112-P19	1-1/8	CP	250 - 50K	10%	0.5%	1.0	340	360 (1)	-55 TO 105	0.35
112-P201	1-1/8	CP	500 - 100K	20%	2.0%	1.0	320	330	-55 TO 105	0.6
125-M44	1-1/4	WW	50 - 50K	5%	2.0%	3.5	315	330	-55 TO 105	1.75
131-M3	1-5/16	WW	50 - 100K	5%	1.0% - 0.3%	3.0	320	330	-55 TO 135	2.0 - 8.0
143-M7	1-7/16	WW	50 - 100K	3%	1.0% - 0.3%	3.5	320	330	-55 TO 135	2.0 - 8.0
143-M8	1-7/16	WW	50 - 100K	3%	0.5% - 0.1%	3.5	352	360 (1)	-55 TO 135	0.6
143-P92	1-7/16	CP	1K - 100K	20%	1.0%	3.0	340	360 (1)	-55 TO 105	1.0
143-P93	1-7/16	CP	1K - 100K	10%	0.5%	3.0	340	360 (1)	-55 TO 105	0.5
175-M110	1-3/4	WW	50 - 100K	5%	1.0%	5.9	320	330	-55 TO 135	2.5
175-M112	1-3/4	WW	10 - 50K	5%	1.0%	5.9	320	330	-55 TO 135	2.6
200-M166	2	WW	50 - 100K	3%	0.4% - 0.06%	5.0	356	360 (1)	-55 TO 135	0.7
200-M167	2	WW	50 - 100K	5%	0.4% - 0.06%	5.0	356	360 (1)	-55 TO 135	0.7
200-M493	2	WW	100 - 100K	5%	0.5%	4.0	320	360 (1)	0 TO 70	0.6
200-M494	2	WW	100 - 100K	5%	0.5%	5.0	320	360 (1)	0 TO 70	0.6
200-M620	2	WW	100 - 100K	5%	0.5%	4.0	320	330	0 TO 70	0.6
200-M865(10)	2	WW	100 - 100K	5%	0.5%	4.0	320	330	0 TO 70	0.6
200-P445	2	CP	1K - 100K	20%	1.0%	2.0	340	360 (1)	-55 TO 105	1.0
200-P446	2	CP	500 - 100K	10%	0.5%	2.0	340	360 (1)	-55 TO 105	0.3
200-P721	2	CP	1K - 100K	20%	1.0%	2.0	320	330	-55 TO 105	1.0
300-M323	3	WW	500 - 100K	5%	0.5%	10.7	320	330	-55 TO 105	4.0
300-M329	3	WW	500 - 200K	5%	0.5%	10.7	320	330	-55 TO 105	4.0
300-M73	3	WW	50 - 100K	3%	0.3% - 0.06%	7.0	358	360 (1)	-55 TO 135	1.0
300-M74	3	WW	50 - 100K	3%	0.3% - 0.05%	7.0	358	360 (1)	-55 TO 135	1.0

1. 360° CONTINUOUS

2. ELEMENT TYPE: WW - WIREWOUND, CP - CONDUCTIVE PLASTIC

Copyright © 2004 maureyinstrument.com All Rights Reserved